


## WAGU® Slide Penstock with Skids GK2

For grouting, with straight sill for grouting  
DN or W x H 1800 x 1800 up to 3000 x 3000



### Available Materials

Frame	Door	Seal	Slide skids	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

### Example for Placing an Order

Slide Penstock with Skids GK2, for grouting, with straight sill for grouting,  
catalogue sheet 07.25, operating gear to corresponding catalogue sheet.


Materials*	Dimensions*
Frame:	DN or width W x H: mm
Door:	Installation depth T: mm <sup>1)</sup>
Seal:	Working pressure: bar
Slide skids:	Flow direction: V/R
Connecting parts:	

<sup>1)</sup> Dimension from penstock invert to upper edge of the structure.


\* Please specify in the enquiry/order.

### Details

Section A-A



Section B-B



Equipped with stem nut  
for low installation depths

Dimensions, Working Pressure,  
and Weights

DN WxH	BR mm	HR mm	LR mm	A mm	St kg	VA kg
1800	2180	4300	300	185	1450	1380
1900	2280	4500	300	185	1610	1530
2000	2380	4700	300	185	1820	1730
2100	2480	4900	300	185	1940	1850
2200	2580	5100	300	185	2180	2080
2300	2680	5300	300	185	2340	2230
2400	2780	5500	300	185	2570	2450
2500	2880	5800	300	185	2790	2650
2600	2980	6000	300	185	3070	2920
2700	3080	6200	300	185	3300	3140
2800	3180	6400	300	185	3540	3370
2900	3280	6600	300	185	3800	3610
3000	3380	6800	300	185	4100	3900

Working pressures higher than 0.6 bar on request