


WAGU® Slide Penstock with Skids GK2

For anchor bolting and sealing by cement mortar, with straight sill for anchor bolting

DN or W x H 1800 x 1800 up to 3000 x 3000



Available Materials

Frame	Door	Seal	Slide skids	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order

Slide Penstock with Skids GK2, for anchor bolting and sealing by cement mortar, with straight sill for anchor bolting, catalogue sheet 07.49, operating gear to corresponding catalogue sheet.


Materials*	Dimensions*
Frame:	DN or width W x H: mm
Door:	Installation depth T: mm ¹⁾
Seal:	Working pressure: bar
Slide skids:	Flow direction: V/R
Connecting parts:	

¹⁾ Dimension from penstock invert to upper edge of the structure.


* Please specify in the enquiry/order.

Details

Section A-A



Section B-B



Equipped with stem nut for low installation depths

Dimensions, Working Pressure, and Weights

DN WxH	BR mm	HR mm	LR mm	A mm	St kg	VA kg
1800	2360	4300	300	185	1450	1380
1900	2460	4500	300	185	1610	1530
2000	2560	4700	300	185	1820	1730
2100	2660	4900	300	185	1940	1850
2200	2760	5100	300	185	2180	2080
2300	2860	5300	300	185	2340	2230
2400	2960	5500	300	185	2570	2450
2500	3060	5800	300	185	2790	2650
2600	3160	6000	300	185	3070	2920
2700	3260	6200	300	185	3300	3140
2800	3260	6400	300	185	3540	3370
2900	3460	6600	300	185	3800	3610
3000	2560	6800	300	185	4100	3900

Working pressures higher than 0.6 bar on request