


WAGU® Slide Penstock with Skids GK1

For grouting, with round sill for grouting
DN or W x H 600 x 600 up to 2000 x 2000



Available Materials

Frame	Door	Seal	Slide skids	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order

Slide Penstock with Skids GK1, for grouting, with round sill for grouting,
catalogue sheet 07.33, operating gear to corresponding catalogue sheet.


Materials*	Dimensions*
Frame:	DN or width W x H: mm
Door:	Installation depth T: mm ¹⁾
Seal:	Working pressure: bar
Slide skids:	Flow direction: V/R
Connecting parts:	

¹⁾ Dimension from penstock invert to upper edge of the structure.


* Please specify in the enquiry/order.

Details

Section A-A



Section B-B



Equipped with stem nut
for low installation depths

Dimensions, Working Pressure,
and Weights

DN WxH	R mm	BR mm	HR mm	LR mm	A mm	St kg	VA kg
600	430	860	1630	185	105	160	150
700	500	960	1850	185	105	190	180
800	570	1060	1920	185	105	230	220
900	640	1160	2290	185	105	270	260
1000	710	1260	2510	185	105	320	300
1100	780	1360	2730	185	105	370	350
1200	850	1460	2950	185	105	430	410
1300	920	1600	3170	190	130	530	500
1400	990	1700	3390	190	130	610	580
1500	1060	1800	3610	190	130	690	660
1600	1140	1900	3840	190	130	820	780
1700	1210	2000	4060	190	130	920	890
1800	1280	2100	4280	190	130	1080	1030
1900	1350	2200	4500	190	130	1190	1130
2000	1420	2300	4720	190	130	1330	1270

Working pressures higher than 0.6 bar on request.