


WAGU® Flap Valve, Circular Type

With lever and counterweight and flange connection
DN 200 to 600



Flange connecting dimensions
to DIN 2501, PN 10 (other connecting
dimensions on request)

Available Materials

Body	Flap	Seal	Counter-weight	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	coated steel	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	coated steel	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	coated steel	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order



Flap Valve, Circular Type, with lever and counterweight and flange connection,
catalogue sheet 12.75.

Materials	Dimensions
Body:	DN: mm
Flap:	Working pressure: bar
Seal:	
Connecting parts:	

* Please specify in the enquiry/order.

Details

Detail X



Dimensions, Working Pressure,
and Weights

DN	PN bar	ØD mm	ØK mm	ØC mm	L mm	R mm	E mm	F mm	G mm	St/VA kg
200	0,6	340	295	290	400	340	250	195	390	22
250	0,6	395	350	340	400	390	250	220	415	28
300	0,6	445	400	390	400	440	250	245	440	35
400	0,6	565	515	490	530	550	330	305	550	45
500	0,6	670	620	590	530	650	330	355	600	90
600	0,6	780	725	690	530	750	330	405	650	120

B = W	width	G	supply line dia.
H	height	St	steel
BR	body width	VA	stainless steel
HR	body height	V	on-seating
LR	body length	R	off-seating
A	distance		

ERHARD - The Answer to Your Valve Problems