


## WAGU® Slide Penstock with Skids GK2

For anchor bolting and sealing by cement mortar, with round sill for grouting

DN or W x H 1800 x 1800 up to 3000 x 3000



### Available Materials

Frame	Door	Seal	Slide skids	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

### Example for Placing an Order

Slide Penstock with Skids GK2, for anchor bolting and sealing by cement mortar, with round sill for grouting, catalogue sheet 07.55, operating gear to corresponding catalogue sheet.


Materials*	Dimensions*
Frame:	DN or width W x H: mm
Door:	Installation depth T: mm <sup>1)</sup>
Seal:	Working pressure: bar
Slide skids:	Flow direction: V/R
Connecting parts:	

<sup>1)</sup> Dimension from penstock invert to upper edge of the structure.


\* Please specify in the enquiry/order.

### Details

Section A-A



Section B-B



Equipped with stem nut for low installation depths

Dimensions, Working Pressure, and Weights

DN WxH	R mm	BR mm	HR mm	LR mm	A mm	St kg	VA kg
1800	1280	2360	4480	300	185	1450	1380
1900	1350	2460	4700	300	185	1610	1530
2000	1420	2560	4820	300	185	1820	1730
2100	1490	2660	5140	300	185	1940	1850
2200	1560	2760	5340	300	185	2180	2080
2300	1630	2860	5580	300	185	1940	1850
2400	1700	2960	5800	300	185	2570	2450
2500	1780	3060	6030	300	185	2790	2650
2600	1840	3160	6240	300	185	3070	2920
2700	1910	3260	6460	300	185	3300	3140
2800	1980	3360	6580	300	185	3540	3370
2900	2050	3460	6900	300	185	3810	3610
3000	2130	3560	7130	300	185	4100	3900

Working pressures higher than 0.6 bar on request