


WAGU® Slide Penstock with Skids GK1

For anchor bolting and sealing by cement mortar, with straight sill for grouting

DN or W x H 600 x 600 up to 2000 x 2000



Available Materials

Frame	Door	Seal	Slide skids	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order

Slide Penstock with Skids GK1, for anchor bolting and sealing by cement mortar, with straight sill for grouting, catalogue sheet 07.47, operating gear to corresponding catalogue sheet.


Materials*	Dimensions*
Frame:	DN or width W x H: mm
Door:	Installation depth T: mm ¹⁾
Seal:	Working pressure: bar
Slide skids:	Flow direction: V/R
Connecting parts:	

¹⁾ Dimension from penstock invert to upper edge of the structure.


* Please specify in the enquiry/order.

Details

Section A-A



Section B-B



Equipped with stem nut for low installation depths

Dimensions, Working Pressure, and Weights

DN WxH	BR bar	HR mm	LR mm	A mm	F mm	St kg	VA kg
600	960	1400	185	105	250	160	150
700	1060	1600	185	105	250	190	180
800	1160	1800	185	105	250	230	220
900	1260	2000	185	105	250	270	260
1000	1360	2200	185	105	250	320	300
1100	1460	2400	185	105	250	370	350
1200	1560	2600	185	105	250	430	410
1300	1750	2900	190	130	250	530	500
1400	1850	3100	190	130	250	610	580
1500	1950	3300	190	130	250	690	660
1600	2050	3500	190	130	250	820	780
1700	2150	3700	190	130	250	920	890
1800	2250	3900	190	130	250	1080	1030
1900	2350	4100	190	130	250	1190	1130
2000	2450	4300	190	130	250	1330	1270

Working pressures higher than 0.6 bar on request