


## WAGU® Flap Valve, Circular Type

With hollow-float flap, for anchor bolting  
DN 700 to 2000



### Available Materials

Body	Flap	Seal	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	S.S. A4

Other materials or combinations available on request.

### Example for Placing an Order


Flap Valve, Circular Type, with hollow-float flap, for anchor bolting,  
catalogue sheet 12.59.

Materials	Dimensions
Body:	DN: mm
Flap:	Working pressure: bar
Seal:	
Connecting parts:	


\* Please specify in the enquiry/order.

### Details


Detail X



Detail X



Design for large dimensions



Dimensions, Working Pressure, and Weights

DN	PN bar	A/B mm	ØC mm	L mm	R mm	E mm	F mm	G mm	St/VA kg
700	0,6	850	790	500	900	300	500	600	160
800	0,6	950	890	500	1000	300	550	650	190
900	0,6	1050	990	600	1100	350	600	700	235
1000	0,6	1150	1090	600	1200	350	650	750	300
1100	0,6	1300	1190	650	1300	400	700	800	355
1200	0,6	1400	1290	650	1400	400	750	850	430
1300	0,6	1500	1480	700	1600	450	850	950	500
1400	0,6	1600	1580	800	1700	500	900	1000	590
1500	0,6	1700	1680	850	1800	550	950	1050	675
1600	0,6	1800	1780	900	1900	600	1000	1100	780
1700	0,6	1900	1880	950	2000	650	1050	1150	920
1800	0,6	2000	1980	1000	2100	700	1100	1200	1060
1900	0,6	2100	2080	1000	2200	700	1150	1250	1240
2000	0,6	2200	2180	1000	2300	700	1200	1300	1450

**ERHARD - The Answer to Your Valve Problems**