


## WAGU® Slide Penstock with Rails GL1

For grouting, with round sill for grouting  
DN or W x H 200 x 200 up to 1600 x 1600



### Available Materials

Frame	Door	Seal	Slide rail	Connecting parts
zinc-plated steel	zinc-plated steel/Al	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

### Example for Placing an Order

Slide Penstock with Rails GL1, for grouting, with round sill for grouting,  
catalogue sheet 07.31, operating gear to corresponding catalogue sheet.


Materials*	Dimensions*
Frame:	DN or width W x H: mm
Door:	Installation depth T: mm <sup>1)</sup>
Seal:	Working pressure: bar
Slide rails:	Flow direction: V/R
Connecting parts:	

<sup>1)</sup> Dimension from penstock invert to upper edge of the structure.


\* Please specify in the enquiry/order.

### Details

Section A-A



Section B-B



Equipped with stem nut  
for low installation depths

Dimensions, Working Pressure,  
and Weights

DN WxH	R mm	BR mm	HR mm	LR mm	A mm	St kg	VA kg
200	140	340	640	140	85	30	28
250	180	390	760	140	85	35	32
300	220	440	870	140	85	40	38
350	250	490	980	140	85	45	42
400	280	540	1080	140	85	50	46
450	320	590	1120	140	85	60	56
500	360	640	1240	140	85	70	65
600	430	740	1530	140	85	85	80
700	500	850	1750	165	105	125	110
800	570	950	1820	165	105	160	140
900	640	1050	2190	165	105	195	175
1000	710	1150	2410	165	105	230	210
1100	780	1250	2630	165	105	260	235
1200	850	1350	2850	165	105	295	270
1300	920	1520	3070	190	130	330	300
1400	990	1620	3290	190	130	390	355
1500	1060	1720	3510	190	130	460	420
1600	1140	1820	3740	190	130	540	500

Working pressures higher than 0.6 bar on request