


WAGU® Slide Penstock with Skids GK1

For grouting, with straight sill for grouting
DN or W x H 600 x 600 up to 2000 x 2000



Available Materials

Frame	Door	Seal	Slide skids	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order

Slide Penstock with Skids GK1 for grouting, with straight sill for grouting,
catalogue sheet 07.23, operating gear to corresponding catalogue sheet.


Materials*	Dimensions*
Frame:	DN or width W x H: mm
Door:	Installation depth T: mm ¹⁾
Seal:	Working pressure: bar
Slide skids:	Flow direction: V/R
Connecting parts:	

¹⁾ Dimension from penstock invert to upper edge of the structure.


* Please specify in the enquiry/order.

Details

Section A-A



Section B-B



Equipped with stem nut
for low installation depths

Dimensions, Working Pressure,
and Weights

DN WxH	BR mm	HR mm	LR mm	A mm	St kg	VA kg
600	860	1400	185	105	160	150
700	960	1600	185	105	190	180
800	1060	1800	185	105	230	220
900	1160	2000	185	105	270	260
1000	1260	2200	185	105	320	300
1100	1360	2400	185	105	370	350
1200	1460	2600	185	105	430	410
1300	1600	2900	190	130	530	500
1400	1700	3100	190	130	610	580
1500	1800	3300	190	130	690	660
1600	1900	3500	190	130	820	780
1700	2000	3700	190	130	920	890
1800	2100	3900	190	130	1080	1030
1900	2200	4100	190	130	1190	1130
2000	2300	4300	190	130	1330	1270

Working pressures higher than 0.6 bar on request