


## WAGU® Flap Valve, Circular Type

With hollow-float flap and flange connection  
DN 200 to 600



### Available Materials

Body	Flap	Seal	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	S.S. A4

Other materials or combinations available on request.

### Example for Placing an Order


Flap Valve, Circular Type, with hollow-float flap and flange connection, catalogue sheet 12.73.

Materials	Dimensions
Body:	DN: mm
Flap:	Working pressure: bar
Seal:	
Connecting parts:	


\* Please specify in the enquiry/order.

### Details

Detail X



Filling plug



### Dimensions, Working Pressure, and Weights

DN	PN bar	ØD mm	ØK mm	ØC mm	L mm	R mm	E mm	F mm	G mm	St/VA kg
200	0,6	340	295	290	400	340	250	195	240	20
250	0,6	395	350	340	400	390	250	220	265	25
300	0,6	445	400	390	400	440	250	245	290	30
400	0,6	565	515	490	530	550	330	305	350	42
500	0,6	670	620	590	530	650	330	355	400	80
600	0,6	780	725	690	530	750	330	405	450	100

<b>B = W</b>	width	<b>G</b>	supply line dia.
<b>H</b>	height	<b>St</b>	steel
<b>BR</b>	body width	<b>VA</b>	stainless steel
<b>HR</b>	body height	<b>V</b>	on-seating
<b>LR</b>	body length	<b>R</b>	off-seating
<b>A</b>	distance		

**ERHARD - The Answer to Your Valve Problems**