


WAGU® Flap Valve, Circular Type

With hollow-float flap and flange connection
DN 700 to 2000



Flange connecting dimensions
to DIN 2501, PN 10 (other connecting
dimensions on request)

Available Materials

Body	Flap	Seal	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order


Flap Valve, Circular Type, with hollow-float flap and flange connection,
catalogue sheet 12.79.

Materials	Dimensions
Body:	DN: mm
Flap:	Working pressure: bar
Seal:	
Connecting parts:	


* Please specify in the enquiry/order.

Details


Detail X



Detail X



Design for large dimensions



Dimensions, Working Pressure, and Weights

DN	PN	ØD	ØK	ØC	L	R	E	F	G	Sr/VA
bar	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
700	0,6	895	840	790	500	900	300	500	600	180
800	0,6	1015	950	890	500	1000	300	550	650	215
900	0,6	1115	1050	990	600	1100	350	600	700	265
1000	0,6	1230	1160	1090	600	1200	350	650	750	335
1200	0,6	1455	1380	1290	650	1400	400	750	850	470
1400	0,6	1675	1590	1580	800	1700	500	900	1000	640
1600	0,6	1915	1820	1780	900	1900	600	1000	1100	850
1800	0,6	2115	2020	1980	1000	2100	700	1100	1200	1140
2000	0,6	2325	2230	2180	1000	2300	700	1200	1300	1540

ERHARD - The Answer to Your Valve Problems