


WAGU® Flap Valve, Circular Type

With hollow-float flap, for anchor bolting
DN 200 to 600



Available Materials

Body	Flap	Seal	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order



Flap Valve, Circular Type, with hollow-float flap, for anchor bolting,
catalogue sheet 12.53.

Materials	Dimensions
Body:	DN: mm
Flap:	Working pressure: bar
Seal:	
Connecting parts:	

* Please specify in the enquiry/order.

Details

Detail X



Dimensions, Working Pressure, and Weights

DN	PN bar	ØD mm	ØK mm	ØC mm	L mm	R mm	E mm	F mm	G mm	St/VA kg
200	0,6	340	295	290	350	340	250	195	240	18
250	0,6	395	350	340	350	390	250	220	265	22
300	0,6	445	400	390	350	440	250	245	290	28
400	0,6	565	515	490	450	550	330	305	350	40
500	0,6	670	620	590	450	650	330	355	400	75
600	0,6	780	725	690	450	750	330	405	450	95

B = W	width	G	supply line dia.
H	height	St	steel
BR	body width	VA	stainless steel
HR	body height	V	on-seating
LR	body length	R	off-seating
A	distance		

ERHARD - The Answer to Your Valve Problems