


WAGU® Flap Valve, Circular Type

With lever and counterweight, for anchor bolting
DN 700 to 2000



Available Materials

Body	Flap	Seal	Counter-weight	Connecting parts
zinc-plated steel	zinc-plated steel	chloroprene	plastic material POM	S.S. A2
S.S. 1.4301	S.S. 1.4301	chloroprene	plastic material POM	S.S. A2
S.S. 1.4571	S.S. 1.4571	chloroprene	plastic material POM	S.S. A4

Other materials or combinations available on request.

Example for Placing an Order


Flap Valve, Circular Type, with lever and counterweight, for anchor bolting,
catalogue sheet 12.511.

Materials	Dimensions
Body:	DN: mm
Flap:	Working pressure: bar
Seal:	
Connecting parts:	


* Please specify in the enquiry/order.

Details


Detail X



Detail X



Design for large dimensions



Dimensions, Working Pressure, and Weights

DN	PN bar	A/B mm	ØC mm	L mm	R mm	E mm	F mm	G mm	StVA kg
700	0,6	850	790	700	900	500	500	800	170
800	0,6	950	890	700	1000	500	550	850	200
900	0,6	1050	990	800	1100	550	600	950	250
1000	0,6	1150	1090	800	1200	550	650	1000	300
1100	0,6	1300	1190	850	1300	600	700	1100	370
1200	0,6	1400	1290	850	1400	600	750	1150	450
1300	0,6	1500	1480	950	1600	700	850	1300	520
1400	0,6	1600	1580	1050	1700	750	900	1400	610
1500	0,6	1700	1680	1100	1800	800	950	1500	700
1600	0,6	1800	1780	1150	1900	850	1000	1600	810
1700	0,6	1900	1880	1200	2000	900	1050	1700	960
1800	0,6	2000	1980	1250	2100	950	1100	1800	1120
1900	0,6	2100	2080	1250	2200	950	1150	1850	1310
2000	0,6	2200	2180	1250	2300	950	1200	1900	1550

ERHARD - The Answer to Your Valve Problems